





VISION - 1.8 COB Indoor Module

Product features:

- ❖ RGB fully flip chip.
- ❖ COB integrated package, can be moisture-proof, dustproof, scrubbing.
- ❖ High contrast, matte fog surface, no reflection.
- ❖ PWM driver IC is configured to support high refresh, and the screen is colorful and realistic.
- ❖ Low voltage drive, low power consumption.
- ❖ Uniform module size: 320mm × 160mm.



Main Technical Specifications:

Parameter	Value
Pixel Pitch	1.86mm
LED Type	Fully flip chip COB
Brightness	600cd/m ²
Module Size	320x160mm
Panel Weight	0.5kg/panel
Pixel Density	288,906pixels/m ²
Pixels Per Panel	172x86pixels
Ingress Protection	Front: IP54
Environment	Indoor
Calibration	Support brightness and chroma
Brightness Control	Manual/Automatic
Color Temperature	1,000K~9,500K Adjustable
Horizontal Viewing Angle	160°
Vertical Viewing Angle	160°
Contrast Ratio	10000:1
Input Power <Max>	280 W/m ²
Input Power <Typical>	125 W/m ²
Input Voltage	AC90~132V/ AC186~264V
Processing Depth	13bit
Refresh Rate	3840Hz
Video Frame Rate	50&60Hz
Input Power Frequency	50~60Hz
LED Life Time	100,000 Hours
Operating Temperature/Humidity	-10°C~45°C / 10%~50%RH
Storage Temperature/Humidity	-20°C~55°C / 10%~60%RH
Certification	/
Data interfaces	HUB320

Note

1. Product pictures are for illustration only, the actual product effects (including but not limited to appearance, color, size) may be slightly different, please refer to the actual product.
2. The specification parameters are reference values. Part of the data comes from Unilumin's internal laboratory and is obtained under a specific test environment. In actual use, it may be slightly different due to product batch differences, configuration differences, software versions, use conditions and environmental factors. Actual usage shall prevail.
3. Different configurations can achieve different refresh rates.